20FT USED WIND & WATERTIGHT SHIPPING CONTAINER FOR SALE

20FT CONTAINERS

CX-CID-61C976 · SKU 29921001f2f0 · Used · Nov 16, 2026



OVERVIEW

Every 20ft unit in this class is built around a welded frame of corten weathering steel, the same alloy used across global shipping fleets for its resistance to rust creep. Corrugated corten panels form the walls and die-stamped sheet forms the roof, all continuously welded to the frame. Underfoot, marine-grade plywood flooring sits on steel cross members, rated for forklift traffic. Double cargo doors swing on heavy hinges and seal against rubber gaskets to keep weather out.

Businesses treat a 20ft unit as square footage on demand: overflow stock, seasonal fixtures, tool cribs and site records all stay secure and dry without a lease or a build-out.

PRODUCT GALLERY

FIG. 1



FIG. 2



PRIMARY USES

- Secure jobsite storage for tools, fasteners and power equipment
- Overflow inventory space behind a retail store or warehouse
- Staging exports and one-way freight loads
- Base shell for a workshop, hobby space or future conversion
- Parts, tires and fluids storage for fleet operations
- Weather-tight shelter for ATVs, mowers and seasonal vehicles

KEY FEATURES

- Forklift-rated marine plywood floor
- Stack-rated structure proven in ocean service
- Fork pockets on most 20ft units for easy repositioning
- Passive wall vents that cut interior condensation
- Original manufacturer data plate retained where present
- Double swing cargo doors that open a full 270 degrees
- Lockrod handles with padlock-ready hasps

BENEFITS

- Wind and water tight when doors are closed and latched
- Ground-level access with no loading dock required
- Hardened steel shell that resists break-ins and rodents
- Relocatable if your site or needs change
- Usable the same day it comes off the truck
- Decades of service life with only basic upkeep

INDUSTRIES SERVED

- Construction
- Municipal
- Logistics
- Agriculture
- Events
- Education
- Manufacturing
- Retail

SPECIFICATIONS AT A GLANCE

CONTAINER ID	CX-CID-61C976
SKU	29921001f2f0
CATEGORY	20ft Containers
CONTAINER SIZE	20ft
CONDITION	Used
CONTAINER GRADE	Wind & Watertight
MATERIAL	Corten Steel
FLOORING	Marine Plywood
DOORS	Double Cargo Doors
VENTILATION	Fitted Air Vents

Full specifications and a dimensional drawing are on this unit's Specification Sheet, available on the product page.

SITE PREPARATION CHECKLIST

- Lay railroad ties, blocks or compacted gravel at the corner points
- Leave swing room in front of the cargo doors, about 6 ft
- Choose a spot with firm, level, well-drained ground
- Check for low wires, branches and eaves along the approach
- Grade so water sheds away from the container, not under it
- Confirm a straight run of clear access for the delivery truck

DELIVERY NOTES

- The truck needs roughly 12 ft of clear width along the approach
- Allow at least 14 ft of overhead clearance for wires and branches
- Tilt-bed placement needs a straight run of about twice the container length
- Have someone 18 or older on site to confirm placement and sign

DOCUMENT CONTROL

DOCUMENT ID	CX-BR-61C976-2026
REVISION	1.0
ISSUE DATE	November 16, 2026
CLASSIFICATION	Technical Specification - Customer Reference

Ready to order or need a custom quote?

(717) 491-6518 · sales@containexco.com · containexco.com